

BATTERY NICKEL-CADMIUM INFORMATION SHEET

MATERIAL SAFETY DATA SHEET

ARTS-Energy Part

Issue K on April 07th, 2023

According to REACH regulation (EC 1907/2006, Art 31) and to OSHA regulation (29 CFR 1910.1200), batteries are ARTICLES with no intended release. As such, they are not covered by legal requirements to generate and supply an SDS or an MSDS. This Battery Information Sheet is provided solely as an information document for the purpose of assisting our customers.

1. Product identification	
Product	Sealed Ni-Cd cells and modules or battery systems composed of these cells
Supplier	ARTS Energy 10 rue Ampère - Zone Industrielle 16440 Nersac FRANCE Tel. No. +33 (0)5 45 90 35 50 Fax No. +33 (0)5 45 90 37 65
Emergency contacts	Chemtrec US Service within the USA : +800 424 93 00 / outside : +1-202-483-7616 for English INRS Orfila : +33(0) 1 45 42 59 59 for French

2. Hazards identification
<p><u>HUMAN HAZARDS :</u> A sealed Nickel-Cadmium cell is not hazardous in normal use when the electrode materials and the electrolyte are content inside the cells. Do not open or burn the products – components or products ingestion could harm the user.</p> <p>Physical Nickel plated steel cans do not present any risk if cells are used for its intended purpose and according to valid directions for use. Do not throw in fire or misuse, as a gas containing hydrogen and oxygen can be generated through the safety valve (explosion risk).</p> <p>Chemical Nickel plated steel cans do not present chemical risk in normal use. In case of misuse (abusive over charge, reverse charge, external short circuit...) and in case of default, some electrolyte can leak from the cell through the safety vent. In these cases, refer to the risk of the alkaline hydroxides. The toxic properties of the electrode materials are hazardous only if the materials are released by mechanical damaging the cell or if exposed to fire.</p> <p><u>ENVIRONMENTAL HAZARDS :</u> Metals used in a Ni-Cd cell have to be collected and recycled through specialized organizations (list on www.rechargebatteries.org).</p>

3. Composition & Information on components

Weight percentage of basic materials : Single cell with steel container

Component	Content (%)*	N° CAS	N° EINEC / ELINC
Active nickel **	10-25	12054-48-7	235-008-5
Active cadmium ***	10-19	21041-95-2	244-168-5
Cobalt	0-2	21041-93-0	244-166-4
Alkaline electrolyte (pH = 14)	14-27	NA	NA
Plastics	3-6	NA	NA
Steel	25-45	NA	NA

* Quantities may vary with cell model

** Active nickel present as Ni(OH)₂ and NiOOH

*** Active cadmium present as Cd(OH)₂ and Cd

Classification of dangerous substances contained into the cells.

Substances				Classification		
Name	N° EC N° CAS N° EINEC	Symbol	Letter	Hazard identification	Special risk (1)	Safety advice (2)
Nickel	028-002-00-7 7440-02-0 231-111-4	Ni	Xn	Nocif	H351, H317, H250	P102, P260, P281
Nickel Hydroxide	028-008-x* 12054-48-7 235-008-5	Ni(OH) ₂	Xn, N	Carc. Cat 3 Harmful	H302/H332, H351, H317, H410	P102, P260, P281, P501
Cobalt Hydroxide	- 21041-93-0 244-166-4	Co(OH) ₂	Xn, N	Harmful	H302, H351, H410	P501
Potassium hydroxide	019-002-00-8 1310-58-3 215-181-3	KOH	C, Xi	Corrosive, Irritant	H314, H302, H319, H335	P305, P280, P309
Sodium Hydroxide	011-002-00-6 1310-73-2 215-185-5	NaOH	C	Corrosive	H314	P305, P280, P309
Lithium Hydroxide	- 1310-65-2 215-183-4	LiOH	C	Corrosive	H314	P305, P280, P309
Cadmium	231-152-8 7440-43-9 -	Cd	T+ N	Carc. Cat. 2; R45. Muta. Cat. 3; R68. Repr. Cat. 3; R62. Repr. Cat. 3; R63 T+; R26. T; R48/23/25 N; R50/53	H330, H341, H350, H361fd, H372, H400, H410	S45, S53, S60, S61

(1) Nature of special risk

H250: Spontaneously flammable in air.
 H302 : Harmful if swallowed.
 H312 : Dangerous in case of skin contact.
 H314 : Causes severe burns.
 H317 : May cause sensitization by skin contact.
 H319 : Sensitization to eyes.
 H330 : Fatal by inhalation
 H332: Harmful if inhaled.
 H335 : Sensitization of the respiratory system.
 H341 : Suspected of inducing genetic abnormalities.
 H350 : May cause cancer
 H351: Suspected carcinogenic effect. Possible risk of irreversible effects.
 H361fd: Suspected to impair fertility or fetus
 H372 (**): Demonstrated risk of serious organ damage from prolonged exposure.
 H400: Highly toxic to aquatic organisms.
 H410: Very toxic to aquatic organisms, possible long-term adverse effect on the aqueous environment.

(2) Security advise

P102: Keep out of reach of children.
 P280 : Wear suitable gloves and eye/face protection.
 P305 : In case of contact with eyes, rinse immediately with plenty of water and seek medical attention.
 P309: In case of accident or if you feel unwell, seek medical attention immediately.
 P501: Dispose of as hazardous material.
 S 24: Avoid contact with skin.
 S 36: Wear suitable protective clothing.
 S 45: In case of accident, consult a medical authority.
 S 60: Dispose as hazardous product.
 S 61: Do not release into the environment. Consult us for information on recycling.
 S 260: Do not breathe dust.

4. First aid measures

In case of electrolyte solution spill (cell leakage) precautions must be taken to avoid any contact of human tissues. If it accidentally happens following must be done:

Inhalation	Fresh air. Rinse mouth and nose with water. Medical treatment
Contact avec la peau	Rinse immediately with plenty of water. Medical treatment.
Contact avec les yeux	Rinse immediately with plenty of water during at least 15-30 min. Immediate hospital treatment. Consult eye specialist.
Ingestion	If the injured is fully conscious: plenty of drink, preferably milk. Do not induce vomiting. Immediate Hospital treatment should be done.

5. Firefighting measures

Extinguishing media





Suitable: Class D-Dry chemical, sand, CO₂.
Not to be used: Water.

Special exposure hazards

Cells can be overheated by an external source or by internal shorting and release alkaline electrolyte mist or liquid. Electrolyte reacts with zinc, aluminum, tin and other active materials releasing flammable hydrogen gas.
In case of PVC sleeved products, the combustion releases chloride gas.

Special protective equipment

Use self-contained breathing apparatus and full fire-fighting protective clothing.

	Respiratory protection	Fire fighters should wear self-contained apparatus.
	Hand protection	Use polypropylene, polyethylene, rubber or Viton gloves when handling leaking or ruptured cells.
	Eye protection	In case of incident or after an abusive use, in case of a leak or cell opening, wear safety glasses with protected side shields or a mask covering the whole face when handling leaking or ruptured cells.
	Other	In the event if leakage or ruptured cells, wear a rubber apron and protective clothes.

6. Spill management procedure

The sealed Ni-Cd cells when sleeved are safe in case of spilling.

Non-sleeved cells may generate short-circuits, causing release of alkaline electrolyte mist or liquid. Electrolyte reacts with zinc, aluminum, tin and other active materials releasing flammable hydrogen gas.

Individual protections and equipment

In such a case, use self-contained breathing apparatus and protective clothing.

Environnemental precautions

No urgency measure requested.

Cleaning

Collect the cells for recycling respecting the local law, if necessary, use sawdust to absorb electrolyte leakages.

7. Handling and storage

Manipulation	<i>Do not allow children to replace batteries without adult supervision.</i> In normal use conditions, no safety rule is specified to handle the cells. Please apply ARTS ENERGY usage instructions.
Stockage	It is recommended to store following ARTS ENERGY specifications in order to ensure longer usage: +5 to +25°C in a 65 +- 5% relative humidity.

8. Exposure controls / Personal protection

Under normal condition of use and handling no special protection is required for sealed Ni-Cd cells.
Protection equipment: it is recommended to wear gloves, or to remove rings and metallic objects to avoid short-circuiting the cells.

9. Physical and Chemical properties

Apparence	Nickel plated steel cylindrical cell eventually sleeved. Dimensions and color according to specification.
Temperature range	Usage recommended between -40°C and +70°C. Risk of electrolyte leakage over 100°C
Specific energy	30 to 60 Wh/Kg
Specific instant power	Up to 1000 W/Kg during 1 second
Mecanical resistance	According to mechanical tests in IEC 61951-1 standard.

10. Stability and reactivity

Conditions	<p>Ni-Cd cells are stable in storage. In case of storage in humid atmosphere, some rust may appear on the product. In case of storage in a charged state, cells progressively lose their energy, generating eventually a progressive temperature increase according to the thermal insulation efficiency of the packaging. In case of exposure to temperature over 100°C, a risk of release of alkaline electrolyte mist or liquid is created. At a higher temperature (160°C) the plastics used can melt or decompose (Polyamide gasket, rubber valve, PVC sleeve...).</p> <p>In case of mechanical deterioration of the cells, active materials contained as powder can be dispersed (Nickel, Cobalt, Zinc, Cadmium).</p>
Hazardous decomposition products	<p>Electrolyte solution is corrosive to all human tissues and will react violently with many organic chemicals. Electrolyte solution reacts with zinc, aluminum, tin and other materials releasing flammable hydrogen gas.</p>

11. Toxicological information

Substances			Hazards		
Name	N° EC N° CAS N° EINEC	Symbol	Effets	Hazards identification	Cancerogenicity Mutagenicity Reprotoxicity
Nickel	028-002-00-7 7440-02-0 231-111-4	Ni	Xn	Nocif	H351, H317, H250
Nickel Hydroxide	028-008-x* 12054-48-7 235-008-5	Ni(OH) ₂	LD50/oral/rat : 1600 mg/kg	VME: 1000µg/m ³ VLE: /	Occupationnal
Cobalt Hydroxide	- 21041-93-0 244-166-4	Co(OH) ₂	LD50/oral/rat : 795 mg/kg	VME: 100µg/m ³ VLE: /	
Alkaline hydroxide	019-002-00-8 1310-58-3 -	KOH NaOH LiOH	LD50/oral/rat : 365 mg/kg	KOH VME: 2µg/m ³ NaOH VME: 2µg/m ³ LiOH VME: 25µg/m ³	
Cadmium	231-152-8 7440-43-9 -	Cd	LD59/ORAL/ RAT : 225 mg/kg	EU : 4 µg/m ³ for alveolar particles (size < 10 µm)	Carc. Cat. 2; R45. Muta. Cat. 3; R68. Repr. Cat. 3; R62. Repr. Cat. 3; R63 T+; R26. T; R48/23/25 N; R50/53

12. Information éco toxicologique

The sealed Ni-CD cells as a product are not presenting Eco toxicological hazards. In case of product destruction or opening, the substances described in paragraph 10 can come in contact of the environment. The metals content in a Ni-CD battery are toxics for the environment.

If not recycled, it must be disposed of in accordance with all state and local regulations.

13. Disposal considerations

Incineration

Never incinerate Ni-Cd batteries.

Landfill

Never dispose Ni-Cd batteries as landfill.

Recycling

Nickel Cadmium batteries can be fully recyclable. They are submitted to the European community directive 91-157/CE. ARTS Energy recommends proper recycling of these batteries whenever possible. You may refer to the following web page for further information and guidance : www.oecd.org/document/44/0,3343,en_2649_34371_1944748_1_1_1_1,00.html (1).

You can also contact ARTS Energy.

- (1) This page provides links to different National Battery Associations and National Collection & Recycling Organizations that can provide you with the latest update on collection & recycling in their respective Countries.



14. Transport information

Sealed Nickel Cadmium batteries are considered to be "dry cell" batteries and are not assigned to dangerous goods regulation for the purpose of transportation by the International Air Transport Association (IATA). International air transport is not restricted provided that, as stated in IATA special provision A164, batteries and battery powered devices/equipment being transported by air are protected from short-circuits.

Our packaging are specially designed to avoid any contact between batteries poles. Furthermore, our cells' cans can bear falls from more than 1.80 m, keeping a good aspect (no electrolyte leakage, no cracks in conformance with the special provision A67 and packing Instructions 872 tests requirements).

Our products are also compliant with the requirement of 55 ° C high temperature test: no electrolyte escapes the batteries in case of shock because their container (nickel-plated steel bucket) is designed to resist to such stress. Finally, our batteries are designed to withstand the vibration and differential pressure variations described in Packing Instruction 872.

ARTS ENERGY Ni-Cd batteries are classified as UN 2800 because they are recognized as reversible according to DS 238. Road transport in Europe of new or used cells and batteries with classification UN2800 (Class 8) is not restricted according to ADR special provision 598, providing that requirements of this special provision are met.

In order to be able to send our batteries by ship, they comply with the DS238 of the IMDG code.

15. Regulatory Information

Nickel-Cadmium batteries are submitted to the European community directive 91-157/CE for recycling.

Substances contained are submitted to the REACH 06-1907/CE regulation.

16. Other information

Consult ARTS ENERGY specifications and precautions of use for optimized use.

The information has been gathered from sources considered reliable and was the extent of our knowledge, accurate and reliable at the date of issue of this document.

However, they cannot be considered completely comprehensive. This information does not imply an implicit or specific guarantee.

This information affects the specific products ARTS Energy and may not be valid for such products used in combination with other materials or in any application or process. It is the responsibility of the user to ensure the relevance of the information on the final use of the product.

ARTS Energy will not accept liability for any loss or damage that may occur, whether direct, indirect, incidental or consequential, from the use of this BIS form. This is a service to our customers.

ARTS Energy does not offer warranty against patent infringement.