

2217 LED ATEX Specifications

Unit Information

Model #: 2217LED ATEX / Item #16460
UPC-IC (12 Digit): 016731164607

Master Pack Dimensions

Weight: 9.9 lbs. (4.5 kg)
Cube: 1.43 ft³ (0.04 m³)
Quantity: 24

Specifications

Power Source: 2x 'D' Cell Alkaline
Light Source: LED
Life: 30,000 hrs
Runtime: 200 hrs
Light Output: 50 Lumens/ 2,450 Candelas
Beam Distance: 99 Meters
Weight (Without batteries): 5.0 oz (.13 kg)

Product Features

- For use in hazardous atmospheres
- 'S' Biner included for quick attachment
- Waterproof, IP67 rating
- 'Switch Guard' Prevents accidental lighting
- Three-way switch : On-Momentary-Off
- Anti-roll tube

Unit Dimensions

Length: 8.1 in. (20.6 cm)
Width: 2.3 in. (5.8 cm) at head

Safety Approvals

IECEx Protection Methods:

Ex ia IIB T3 Ga
Ex ia IIIB T145°C Da
-5°C ≤ +40°C

ATEX Protection Methods:

Ex II 1GD Ex ia IIB T3 Ga Ex ia IIIB T145°C Da -5°C ≤Ta ≤+40°C

ZONE 0 BASEEFA

Approved For use with Duracell MN1300 or Energizer E95 cells only



WorkSafe™ Model # 2217LED ATEX

