

## ***2217LED Specifications***

### **Unit Information**

Model #: 2217LED / Item #15460  
UPC-IC (12 Digit): 016731154608

### **Unit Dimensions**

Length: 8.1 in. (20.6 cm)  
Width: 2.3 in. (5.8 cm) at head

### **Master Pack Dimensions**

Weight: 9.9 lbs. (4.5 kg)  
Cube: 1.43 ft<sup>3</sup> (0.04 m<sup>3</sup>)  
Quantity: 24

### **Specifications**

Power Source: 2x D Cell Alkaline  
Light Source: LED  
Life: 30,000 hrs  
Runtime: 200 hrs  
Light Output: 50 Lumens  
Beam Distance: 88 Meters  
Weight (Without batteries): 5.0 oz (.13 kg)

### **Safety Approvals**

UL Protection Methods  
Intrinsically Safe  
Divisions 1 & 2  
Class I, II, III Div 1 Groups A-G  
Class I, II, III Div 2 Groups A-G  
Operating Temp T5

### **Product Features**

- For use in hazardous atmospheres
- S Biner included for quick attachment
- Waterproof, IP67 rating
- Switch Guard Prevents accidental lighting
- Three-way switch : On-Momentary-Off
- Anti-roll tube
- Faceted reflector for more light



**WorkSafe™ Model # 2217LED**

### **Accessories**

23853	6 ½ Red Snap In Wand
23860	6 ½ Yellow Snap In Wand

### **Description**

