# 2AA ATEX **Energizer**

## **European Region**

## **Product Detail:**

**Designation:** Energizer

2AA ATEX

**SAP:** 628908

Colour: Safety Orange and Black

Power Source: Two "AA"

IEC: LR6

Lamp: Three White LEDs

Lamp Life (hr): Lifetime
Light Output (lumens): 40
Run Time (h:min): 12
Beam Distance (m): 52

Peak Beam Intensity (cd): 676

**Durability:** Survives 1-meter drop

Typical Weight: 66 grams

(without batteries)


**Dimensions (mm):** 151.6 x 35.1 x 40.6

## Performance:

35.1 mm

#### Run Time Continuous Drain to

Continuous Drain to End of Useable Light (21°C)



Battery Type

Tested according to ANSI/NEMA FL 1 Standards.

## **Important Notice**

This datasheet contains information specific to products manufactured at the time of its publication

Contents herein do not constitute a warranty

©Energizer / All Rights Reserved

# INTRINSICALLY SAFE





· Division 1, Class 1 rated

## **WATERPROOF**

- Meets IEC 60529 IPX7 standards
- Continues to operate after submersion in 1 metre of water for 30 minutes



## **IMPACT RESISTANT**

- Survives a 1-metre drop
- Shatterproof lens



## **RELIABLE**

 12 hour run time using Energizer<sub>®</sub> MAX<sup>®</sup> batteries



### UL/CUL intrinsic safety for hazardous locations Class I Div. 1 Groups A,B,C, & D, Class II Div. 1 Groups E,F,&G, and Class III Div. 1; T4.

628908

Approved by global safety agencies, the is

ideal for work in harsh conditions. The

Energizer<sub>®</sub> 2AA ATEX torch is waterproof,

dustproof and survives a 1-metre drop

A built-in carabiner belt clip makes for

easy access, while the internationally

approved orange safety color provides

instant recognition. The White LED lamps

supply steady, bright illumination for

about 12 hours between battery changes

(using Energizer<sub>®</sub> MAX<sup>®</sup> batteries).

European Region

- MSHA for methane-air mixtures.
- ATEX intrinsically safe flashlight for ξx IM2/II1G EEx ia I/IIC T4
- IECEx intrinsically safe flashlight for Ex ia IIC T4
- -20°C to 40°C ambient operating range.
- € 0539

test.

• EN60529 ingress protection level IP67.

#### **Before Using Your Flashlight:**

Please read all instructions and cautionary markings on the package and light