

# LED Luminaires with Strip - 1x40W 120cm 4800lm 4000K IP65 IK08



- ♦ Quick and easy installation
- ♦ Water resistant
- ♦ 120cm

A high quality LED fixture with integrated LED strip instead of LED tube. This makes the installation even easier. Link this LED bar together to illuminate a larger space at once. The dust and low pressure water jets protected luminaire (IP65) and the robust impact-resistant polycarbonate housing (IK08) make this luminaire very suitable for damp rooms such as garages, barns, basements, production and market halls. This fixture has a brightness of 4800 lumens, a color temperature of 4000K and an energy consumption of 40W. This product is supplied with 2 connections for wiring through. Environmentally friendly due to low energy consumption and long lifespan.

Article number LLW2400229\_01

EAN 8719323782730

Brand

LED's light PRO

## General

Warranty	2-Year
Collection	Functional
Compliance certificates	CE
PLC Status	Active

## Lighting

Photobiological safety according to EN 62471	RG1
Light color category	Neutral white
Color rendering index	80
Flicker-free	No
Beam angle	120 °
Total lumens	4800 lm
Color consistency (McAdam ellipse)	SDCM6
Light sharing	Symmetric
Color temperature	4000 K
Lamp efficacy	120

## Performance

Rated life time L80/B10 at 25 C	30000 h
Impact strength	IK08
Rated life time L70/B50 at 25 C	50000 h

Energy class (EU 2019/2015)	D
Energy class (EU 874/2012)	A++
IP Rating	IP65

## Mechanical

Article width	77 mm
Article height	61 mm
With light source	No
Color housing	White
Article length	1200 mm
Housing material	Polycarbonate (PC)
Lamp socket	G13

**Electrical**

<b>Input current</b>	<b>190 mA</b>
<b>Control gear type</b>	<b>Non-isolated driver</b>
<b>Type of dimming</b>	<b>Not dimmable</b>
<b>Input frequency</b>	<b>50/60 Hz</b>
<b>LED chip brand</b>	<b>Other</b>
<b>LED chip quantity</b>	<b>136</b>
<b>LED chip type</b>	<b>SMD 2835</b>
<b>Nominal voltage</b>	<b>220 — 240 V</b>
<b>Power consumption</b>	<b>40.0 W</b>
<b>Voltage type</b>	<b>AC</b>
<b>Total harmonic distortion (THD)</b>	<b>20.00</b>
<b>Glow wire test</b>	<b>650 °C</b>

**Di"user finishing****Article net weight****Difuser material****Opal****1250 g****Polycarbonate (PC)****Logistic data**

<b>CBM master carton</b>	<b>0.11 m<sup>3</sup></b>
<b>Packaging height</b>	<b>6.5 cm</b>
<b>Packaging width</b>	<b>7.5 cm</b>
<b>Packaging length</b>	<b>121.0 cm</b>
<b>HS Code</b>	<b>9405920090</b>
<b>Packaging gross weight</b>	<b>1220.0 g</b>
<b>Packaging paper material weight</b>	<b>40.0 g</b>
<b>EAN Product</b>	<b>8719323782730</b>
<b>Packaging plastic material weight</b>	<b>9.00 g</b>
<b>HS Code_old</b>	<b>9405920090</b>
<b>Master carton quantity</b>	<b>15</b>
<b>Master carton width</b>	<b>25 cm</b>
<b>Master carton length</b>	<b>124 cm</b>
<b>Master carton height</b>	<b>34 cm</b>
<b>Master carton gross weight</b>	<b>19.16 kg</b>
<b>Master carton paper material weight</b>	<b>1420.00 g</b>
<b>Master carton plastic material weight</b>	<b>135.00 g</b>