



0300271 Work Light - 50W 4500lm 4000K IP65 - Rough service - Protection class II

- Anti-glare cover
- Rough service tested
- Dust tight and waterjet protected

The work light is perfect for places where a mobile and bright light source is needed, such as on construction sites, during installation work, in workshops or in workplaces. For hobby craftsmen as well as professionals.

The LED work light has a modern and robust aluminum housing and is equipped with a convenient ergonomically shaped handle. The lamp has a five-meter-long cable, meaning that it can easily be moved around the room.

LED's work

The light emits a neutral white light and the cover makes sure that there is no glare and the light is evenly distributed. Furthermore, the light has a high impact resistance and is rough service tested, making it perfect for use on construction sites. The lamp is highly dust tight and waterjet protected.



General

Brand	LED's work
Collection	Functional
PLC Status	Active
Warranty	2-Year

Lighting

Total lumens	4500 lm
--------------	---------

Useful lumens	4500 lm
Lamp efficacy	90
Color temperature	4000 K
Color description	Neutral white
Color rendering index	80
Color consistency (McAdam Ellipse)	SDCM6
Beam angle	110 °
Flicker-free	Yes

Electrical

Power consumption	50 W
Input voltage.	220 — 240 V
Voltage type	AC
Input frequency	50/60 Hz
Power factor	0.9
Input current.	240 — 240 mA
Safety class	II
Control gear type	Driver on board
Control gear mounting	On PCB
Type of dimming	Not dimmable
Glow wire test	650 °C
LED chip type	SMD 2835
LED chip brand	Sanan
LED chip quantity	50

Power Supply

Brand of power supply	OEM
-----------------------	-----

Performance

IP Rating	IP65
Impact strength	IK08
Rough service	Yes
Rated life time L70/B50 at 25 C	30000 h
Operating Temperature	-25 — 40 °C
Energy class (EU 874/2012)	A+
Energy class (EU 2019/2015)	F

Mechanical

With light source	No
Article length	214 mm
Article width	220 mm
Article height	310 mm
Article net weight	1730 g
Housing material	Aluminum
Color housing	Black
Diffuser material	Polycarbonate (PC)
Diffuser finishing	Opal
Cable type	H07RN-F 2X1.0 mm ²
Cable length	500 cm
Cable color	Black
Plug type	Contour plug
Type of gland	M16 Plastic
Lamp socket	N/A
Lamp type	LED not exchangeable

Logistic Data

Packaging length	22.5 cm
Packaging width	11 cm
Packaging height	29 cm
Packaging gross weight	1950 g
EAN Product	8720246200164
Packaging paper material weight	133 g
Packaging plastic material weight	5 g
Master carton length	47 cm
Master carton width	34 cm
Master carton height	31 cm
CBM master carton	0.049538 m ³
Master carton quantity	6
Master carton gross weight	12.27 kg
Master carton paper material weight	1860 g
Master carton plastic material weight	30 g
Country of Origin	CN
HS Code	9405421000