

Warning Lamp Euro-Nitra LED

tested according to German Standards

- Lamp class L7 (one-sided) resp. L6 (two-sided) according to EN 12352
- High-quality LEDs with nearly unlimited life time
- Lens diameter 190 mm, lamp head adjustable
- Automatic solar switch
- Easy battery replacement without removing the lamp
- Easy attachment to tubes or barriers with the firmly mounted bracket
- Loop for carrying
- Examples of application (depending on country-specific regulations)
 - at barriers
 - at site fences
 - on beacons
 - on folding traffic signs
 - on traffic cones

Warning Lamp Euro-Nitra LED	Ref. No.
Euro-Nitra LED, flashing/steady light, one-sided amber, with bracket	112 127-51
Euro-Nitra LED, flashing/steady light, one-sided red, with bracket	112 127-53
Euro-Nitra LED, flashing/steady light, two-sided amber, with bracket	112 128-51
Euro-Nitra-LED, flashing/steady light, two-sided red, with bracket	112 128-53

Accessories and Spare parts	Ref. No.
NiKo key	070 090-1
Pulser LED, one-sided amber	358 057-21
Pulser LED, one-sided red	358 057-23
Pulser LED, two-sided amber	358 058-21
Pulser LED, two-sided red	358 058-23

Operating time with one set of batteries

With battery Premium 800	steady light 250 hrs flashing light 750 hrs
With battery Premium 3000	steady light 1500 hrs flashing light 4500 hrs
With battery Konstant 45	steady light 1500 hrs flashing light 4500 hrs

Technical data

Light colour	amber resp. red
Eff. light intensity	amber one-sided 24 cd / two-sided 18 cd
Eff. light intensity	red one-sided 22 cd / two-sided 20 cd
Blink-/flash rate	60 fl./min.
Dimensions (LxWxH)	195 x 90 x 350 mm

Packaging unit

8 lamps in one carton / 200 lamps on one pallet
also available in other quantities



Euro-Nitra LED



Euro-Nitra LED with bracket



NiKo key



Changing battery