



9455 RALS



Introducing the Peli 9455 RALS, the world's first Class I Division 1, ATEX Zone 0 and IECEx ia safety certified remote area light. Now you can take remote area lighting to hazardous areas around the globe.

The 125° beam angle along with up to 1,600 lumens and providing up to 10 hours of run time, the 9455 will support full work shifts and deliver safe situational awareness. Weighing only 16 pounds and completely collapsible, makes for easy carry and quick set ups. The dual light modes, High/Low provide flexible options and is equipped with a 30 minute visible low battery warning indicator.

From confined spaces to tight manholes, nothing stops the Peli 9455 RALS from illuminating the work site, safely.

****The repair of the 9455 needs to be conducted by a certified Peli Products repair center due to the requirements of the safety certificate.**

Class I Division 1, ATEX Zone 0, IECEx ia safety certified

- Class I Division 1, ATEX Zone 0, IECEx ia safety certifiedUp to 1,600 lumens

- Up to 1,600 lumensUp to 10 hours run time

- Up to 10 hours run timeDuurzaam heroplaadbaar batterijpak

- Duurzaam heroplaadbaar batterijpakHigh / Low lighting modes

- High / Low lighting modesLow battery indicator

- Low battery indicatorHi Vis safety yellow

- Hi Vis safety yellow

CONFIGURATIES

9455 - Standard

AFMETINGEN

Head (L x W x D): 8.26 x 5.71" x 1.97 (21 x 14.5 x 5 cm)

Closed (L x W x D): 15.35 x 7.87" x 9.06 (39 x 20 x 23 cm)

Mast Length: 31.50"

Cord Length: 12.60"

MATERIAAL

Body: Polycarbonate (PC) / ABS

Head: Aluminum

Lens: Polycarbonate (PC)

KLEUREN



High Visibility Yellow

LIGHT SPECS

Lumens (High): 1600

Lumens (Low): 800

Lamp Type: LED

Number of LEDs: 10

Lamp Life: 50000 hrs

Beam Spread: 125°

IP Rating: 54

POWER

Run Time (High): 5.00 hrs

Run Time (Low): 10.00 hrs

Battery Type: NiMH

Battery Lifespan: 300 cycles

Charge Time: 480 mins

Battery Level Indicator: Low battery warning

Watts: 21 W

Volts: 10.8v

WEIGHT

Weight: 16.00 lbs

SWITCH

Switch Type: Silicone Rubber Keypad

Light Modes: High / Low / Flashing

CERTIFICERINGEN

IECEEx ia

Class I, Division 1

ATEX Zone 0

Peli Products, S.L.U.

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com