



Save as PDF
NEW



SabreLite™ 2010 LED Zone 0 Flashlight



The SabreLite 2010 LED is Peli's flagship LED torch. The rugged, light weight ABS resin body is submersible to 150 meters and a twist on/off lens shroud eliminates accidental discharge. It is powered by 3 C alkaline cells. The SabreLite 2010 is the future of LEDs. Certified to ATEX Zone 0 (Category 1).



SabreLite™ 2010 LED Zone 0 Flashlight

ANSI FL1 Specifications

LIGHT SOURCE.	High	
	LED	
BATTERIES	3 C Alkaline (Not included)	
CHARGE TIME	N/A	
VOLTAGE	4.5	
LENGTH	20.6 cm (8.11")	
WEIGHT W/ BATTERIES	0.13 kg (4.5 oz.)	
WEIGHT W/O BATTERIES	0.15 kg (5.36 oz.)	

LIGHT OUTPUT

RUNTIME (hours/min)

BEAM DISTANCE (meters)

PEAK BEAM INTENSITY (candela)

WATER RESISTANT

FL 1 STANDARD	High	
	32h	
	144m	

Approvals

CE Ex - II 1 G Ex ia IIC T4 Ga (Energizer E93), 145°C Ga (Duracell MN1400), T3 Ga (Panasonic LR14), II 1 D Ex ia IIIC T135°C (Energizer)
Certificate: ITS11ATEX27782

Materials

Body	Lens	Shroud	Switch Type
EXL	PC	ABS	Twist On/Off Lens Shroud
Clip	Contact, Spring & Retainer	O-Ring	Night Vision Film
ABS	Stainless Steel and Brass Nickel	Ethylene Propylene	N/A

Configuration

Cat. #	Description
2010Z0	SabreLite™ 2010 LED Zone 0 Flashlight

SabreLite™ 2010 LED Zone 0 Flashlight Accessories

No accessories are currently available for this product