

Uncontrolled document as of July 24, 2013. Refer to website for up to date specifications.



Save as PDF



## Peli lights - LED technology lights

Version rechargeable de la StealthLite™ 2410 LED™. La StealthLite Rechargeable LED 2460 utilise un bloc-batterie NiMH de longue durée qui garantit une durée d'éclairage étendue. Elle est fournie avec une base de recharge qui peut être installée à domicile ou au bureau en utilisant le transformateur de 220 V ou dans un véhicule à l'aide d'un câblage direct ou d'une prise de 12 V. Elle est certifiée par ATEX Zone 1 (Catégorie 2).



### Peli lights - LED technology lights

#### ANSI FL1 Specifications

	Fort
<b>SOURCE DE LUMIÈRE</b>	LED
<b>PILES</b>	4 AA NiMH (Included)
<b>TEMPS-CHARGE</b>	NiMH Battery Pack 2-3 hrs.
<b>TENSION</b>	4.8
<b>LONGUEUR</b>	17.8 cm (7")
<b>POIDS AVEC PILES</b>	0.14 kg (4.8 oz.)
<b>POIDS SANS PILES</b>	0.12 kg (4.4 oz.)
	Fort

**RENDEMENT LUMINEUX**

#### Materials

Corps	Lentille	Revêtement de la lentille	Genre d'interrupteur
Anti-static ABS	Polycarbonate Resin	ABS	One-handed safety switch operation
Pince	Contact, ressort et fixation	Joint torique	Disques de vision nocturne
N/A	Stainless Steel and Phosphore Bronze	Ethylene Propylene	N/A

#### Configuration

Cat. n°	Description
---------	-------------

### Peli lights - LED technology lights ACCESSOIRES

No accessories are currently available for this product

**PORTÉE DE  
FAISCEAU  
(mètre)**

**INTENSITÉ DU  
FAISCEAU  
MAXIMUM  
(candela)**

	4h 30m	
	153m	
	1583cd	

FL 1 STANDARD		
		
		
		
		

### Homologations

CE  - II 2 G Ex ib IIC T4 Gb

Certificate: EPSILON 07ATEX2168X