

Product Data Sheet Model No.: 079187-LA

Product Category Series Description Electrical characteristics Input Voltage Operating Voltage Standby Current Lamp current Battery Operation Lighting characteristics CCT Iuminous flux / Intensity LED Type Light modes Light duration in auto mode		LED cordless light SafeGuard RF3.1 LED outdoor automotive motion sensor security light, one headlamp 4.5VDC (3 x 1.5V C batteries) 4.5V < 100µA 350mA 600 days* (Based on 5 operation per day in Auto Mode)
Category Series Description Electrical characteristics Input Voltage Operating Voltage Standby Current Lamp current Battery Operation Lighting characteristics CCT Iuminous flux / Intensity LED Type Light modes		LED cordless light SafeGuard RF3.1 LED outdoor automotive motion sensor security light, one headlamp 4.5VDC (3 x 1.5V C batteries) 4.5V < 100µA 350mA
Category Series Description Electrical characteristics Input Voltage Deperating Voltage Standby Current Lamp current Battery Operation Lighting characteristics CCT uminous flux / Intensity LED Type Light modes		LED cordless light SafeGuard RF3.1 LED outdoor automotive motion sensor security light, one headlamp 4.5VDC (3 x 1.5V C batteries) 4.5V < 100µA 350mA
Category Series Description Electrical characteristics nput Voltage Deperating Voltage Standby Current Lamp current Battery Operation Lighting characteristics CCT uminous flux / Intensity LED Type Light modes		SafeGuard RF3.1 LED outdoor automotive motion sensor security light, one headlamp 4.5VDC (3 x 1.5V C batteries) 4.5V < 100µA 350mA
Category Series Description Electrical characteristics Input Voltage Operating Voltage Standby Current Lamp current Battery Operation Lighting characteristics CCT uminous flux / Intensity LED Type Light modes		SafeGuard RF3.1 LED outdoor automotive motion sensor security light, one headlamp 4.5VDC (3 x 1.5V C batteries) 4.5V < 100µA 350mA
Series Description Electrical characteristics Input Voltage Operating Voltage Standby Current Lamp current Battery Operation Lighting characteristics CCT Iuminous flux / Intensity LED Type Light modes		SafeGuard RF3.1 LED outdoor automotive motion sensor security light, one headlamp 4.5VDC (3 x 1.5V C batteries) 4.5V < 100µA 350mA
Description Electrical characteristics Input Voltage Operating Voltage Standby Current Lamp current Battery Operation Lighting characteristics CCT uminous flux / Intensity LED Type Light modes		LED outdoor automotive motion sensor security light, one headlamp 4.5VDC (3 x 1.5V C batteries) 4.5V < 100μA 350mA
Electrical characteristics Input Voltage Operating Voltage Standby Current Lamp current Battery Operation Lighting characteristics CCT Iuminous flux / Intensity LED Type Light modes		4.5VDC (3 x 1.5V C batteries) 4.5V < 100μA 350mA
Input Voltage Operating Voltage Standby Current Lamp current Battery Operation Lighting characteristics CCT Iuminous flux / Intensity LED Type Light modes		4.5V < 100μA 350mA
Input Voltage Operating Voltage Standby Current Lamp current Battery Operation Lighting characteristics CCT Iuminous flux / Intensity LED Type Light modes		4.5V < 100μA 350mA
Operating Voltage Standby Current Lamp current Battery Operation Lighting characteristics CCT Iuminous flux / Intensity LED Type Light modes		4.5V < 100μA 350mA
Standby Current Lamp current Battery Operation Lighting characteristics CCT uminous flux / Intensity LED Type Light modes		< 100μA 350mA
Lamp current Battery Operation Lighting characteristics CCT uminous flux / Intensity LED Type Light modes		350mA
Lighting characteristics CCT uminous flux / Intensity LED Type Light modes		
Lighting characteristics CCT luminous flux / Intensity LED Type Light modes		boo days (based on 5 operation per day in Auto Mode)
		4500K-5500K ≥ 130 lm 1 x SMD LED
light duration in auto mode		OFF / ON / AUTO
		10 s ±3 s
Sensors characteristics		
Sensor		Photo sensors & PIR Sensors
Sensor Detection Range		8M, 110°
Lux Detection Frequency		3 sec per detecion, 1 sec between detection
Trigger Lux Value		0-35 Lux Adjustable
Physical Characteristics	;	
Operating Temperature		-20°C to 50°C
Storage Temperature		-20°C to 50°C
Dimension		96.0 (L) x 201.1 (H) x 129.9 (D) mm
Veight		
Housing Material		PC
P Rating		IP55
Product Compliance		CE, RoHS
Warranty		12 months from ex-factory date
Based on new alkaline batt	tteries. Do not mix n	new and old batteries at the same time.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

S-LA-160506-033 R1